

Wave Amplification in a Magnetic Medium

Kirk T. McDonald

Joseph Henry Laboratories, Princeton University, Princeton, NJ 08544

(May 1, 1979)

1 Problem

One way to prepare an optically active medium is to turn on a strong DC magnetic field at right angles to a static magnetic field that has initially aligned the dipoles of a magnetic medium. Then the dipoles will precess about the direction of the strong magnetic field, before eventually relaxing into alignment with that field. During those intervals while the dipoles \mathbf{m} are antialigned with the initial static field, they are in a state of high energy $U = -\mathbf{m} \cdot \mathbf{B}$. When in this state, the medium can give up energy to a probe electromagnetic wave (with magnetic field along the direction of the strong DC field), thereby amplifying it.

Deduce the equations of motion for the magnetization $\mathbf{M} = N\mathbf{m}$ of a medium that consists of N permanent dipoles \mathbf{m} (with angular momentum $\mathbf{L} = \Gamma\mathbf{m}$) per unit volume when the medium is immersed in a magnetic field \mathbf{B} . Consider the specific example of a static magnetic field $B_{0x}\hat{\mathbf{x}} + B_{0y}\hat{\mathbf{y}}$ where $B_{0x} \ll B_{0y}$, and an oscillatory field $B_y e^{-i\omega t}\hat{\mathbf{y}}$. You may suppose that $M \ll B_x$ and $M \ll B_y$.

A measure of the ability of the medium to amplify a probe wave is the frequency-dependent index of refraction $n(\omega) = \sqrt{\mu}$, where μ is the magnetic susceptibility related by $\mathbf{B} = \mu\mathbf{H} = \mathbf{H} + 4\pi\mathbf{M}$ (in Gaussian units, and in a medium of dielectric constant $\epsilon = 1$). In the present example, the wave field has magnetic field along the y axis, so that you can write

$$B_y(\omega) = \mu H_y(\omega) = H_y \left(1 + 4\pi \frac{M_y}{H_y} \right), \quad (1)$$

Since we assume that $M \ll B_y$, we also have $M_y \ll H_y$, and the index of refraction is given by

$$n(\omega) = \sqrt{\mu} \approx 1 + 2\pi \frac{M_y}{H_y}. \quad (2)$$

If the medium is to exchange energy with a wave, there must be additional processes occurring. For index of refraction to include absorption (or amplification), it suffices to suppose that there is a kind of damping mechanism that aligns the magnetic dipoles with the static magnetic field. A phenomenological form for this is

$$\frac{d\mathbf{m}}{dt} = \gamma(\hat{\mathbf{m}} \times \hat{\mathbf{B}}) \times \mathbf{m} \approx -\gamma m(\hat{\mathbf{m}} - \hat{\mathbf{y}}), \quad (3)$$

where γ is the damping factor, and the approximation notes that the static field is largely along the y axis. Include this damping in the equations of motion, solve for the oscillatory behavior of $M_y \propto e^{-i\omega t}$ assuming the damping is slow so that $\gamma \ll \Gamma B_x$, and then calculate the index $n(\omega)$. Show that when M_x has precessed to be opposite to B_{0x} , the index of refraction implies amplification of a traveling wave of H_y (and M_y).

2 Solution

The merits of an oscillatory magnetic field transverse to a static magnet field in the study of individual magnetic moments were emphasized by Rabi [1]. Bloch [2] extended this approach to magnetic media, but it was perhaps Dicke [3] who realized that the optically active medium thereby created could lead to “super-radiance”, *i.e.*, to laser beams.

When a magnetic dipole \mathbf{m} is subject to a magnetic field \mathbf{B} it experiences a torque $\mathbf{m} \times \mathbf{B}$ that precesses the angular momentum $\mathbf{L} = \mathbf{m}/\Gamma$, where $\Gamma = m/L$ is the gyromagnetic ratio of the dipole. If the magnetic dipoles are electrons, then $\Gamma = e/2m_e c \approx 10^7$ Hz/gauss, where e and m_e are the charge and mass of the electron, and c is the speed of light. Thus,

$$\mathbf{m} \times \mathbf{B} = \frac{d\mathbf{L}}{dt} = \frac{1}{\Gamma} \frac{d\mathbf{m}}{dt}. \quad (4)$$

The precession frequency is $\Gamma B \approx 10^7 B$ for B in gauss. We will consider magnetic fields $B_y(t)$ of optical frequencies, $\approx 10^{15}$ Hz, so the precession will be very slow compared to the wave frequency.

The equation of motion of a single moment, including the damping (3) of the moment to alignment with the static magnetic field that is predominantly along the y axis, is

$$\frac{d\mathbf{m}}{dt} = \Gamma \mathbf{m} \times \mathbf{B} - \gamma m(\hat{\mathbf{m}} - \hat{\mathbf{y}}). \quad (5)$$

The equation of motion for the magnetization $\mathbf{M} = N\mathbf{m}$ is therefore

$$\frac{d\mathbf{M}}{dt} + \gamma \mathbf{M} = \Gamma \mathbf{M} \times \mathbf{B} + \gamma M \hat{\mathbf{y}}. \quad (6)$$

For a magnetic field $B_{0x}\hat{\mathbf{x}} + (B_{0y} + B_y(t))\hat{\mathbf{y}} = (H_x + 4\pi M_x)\hat{\mathbf{x}} + (H_y + 4\pi M_y)\hat{\mathbf{y}}$, the components of eq. (6) are

$$\frac{dM_x}{dt} + \gamma M_x = -\Gamma M_z B_y, \quad (7)$$

$$\frac{dM_y}{dt} + \gamma M_y = \Gamma M_z B_x + \gamma M, \quad (8)$$

$$\frac{dM_z}{dt} + \gamma M_z = \Gamma(M_x B_y - M_y B_x). \quad (9)$$

The desired physical picture is that the magnetization \mathbf{M} precesses around the y axis (subject to the “slow” damping γ), with the oscillatory magnetization M_y being only a small perturbation about this dominant motion. From eqs. (7) and (9) we see that this is a good approximation so long as $M_y B_x \ll M_x B_y$. We choose B_{0x} to be small compared to B_{0y} , and prepare the medium in an initial state with $M_y \ll M_x$. The latter might be accomplished, for example, by starting with $B_{0y} = 0$ so the dipoles line up with B_{0x} , and then turning on the field B_y quickly; if the damping time is long compared to the precession period, then there is a useful interval during which the desired behavior obtains.

We are principally interested in the behavior of M_y for use in calculating the index of refraction, so we take the derivative of eq. (8), noting that M is constant since the medium

is comprised of permanent dipoles, and insert eq. (9) to find

$$\begin{aligned} \frac{d^2 M_y}{dt^2} + \gamma \frac{dM_y}{dt} &= \Gamma \frac{dM_z}{dt} B_x = \Gamma B_x [\Gamma (M_x B_y - M_y B_x) - \gamma M_z] \\ &= \Gamma^2 B_x (M_x H_y - M_y H_x) - \gamma \left(\frac{dM_y}{dt} + \gamma M_y - \gamma M \right). \end{aligned} \quad (10)$$

Assuming that $M \ll B_x$, then $H_x \approx B_x$ and we may approximate $\Gamma^2 B_x H_x \equiv \omega_0^2$ as being constant ($\omega_0 \approx \Gamma B_x$). Then,

$$\frac{d^2 M_y}{dt^2} + 2\gamma \frac{dM_y}{dt} + (\gamma^2 + \omega_0^2) M_y = \Gamma^2 B_x H_x \frac{M_x}{H_x} H_y + \gamma^2 M = \omega_0^2 \frac{M_x}{H_x} H_y + \gamma^2 M. \quad (11)$$

The term $\gamma^2 M$ leads to a constant component $M_y = \gamma^2 M / (\gamma^2 + \omega_0^2)$, which we can ignore since we assume that the damping constant γ is small compared to the frequency $\omega_0 \approx \Gamma B_x$. Our main interest is the behavior of the system when a wave is present, $H_y = H_{0y} e^{-i\omega t}$ and $M_y = M_{0y} e^{-i\omega t}$, at frequency $\omega \gg \omega_0$, in which case we can regard M_x as effectively constant over a few cycles of the high frequency wave. Inserting this hypothesis in eq. (11), we find that the high-frequency part of M_y obeys

$$M_y = \frac{M_x}{H_x} \frac{\omega_0^2 H_y}{\omega_0^2 - \omega^2 + \gamma^2 - 2i\gamma\omega}. \quad (12)$$

Recall that we need $M_y H_x \ll M_x H_y$ for the dominant behavior of the magnetization to be precession about the y axis. From eq. (12) we see that this would not hold for frequency ω close to ω_0 (since we assume that $\gamma \ll \omega_0$). But we consider ω of optical frequencies, so $\omega \gg \omega_0$ for any reasonable value of B_x , as noted previously.

The index of refraction for a wave propagating in the z direction with magnetic field along the y axis is therefore

$$n(\omega) = \sqrt{\mu} \approx 1 + 2\pi \frac{M_y}{H_y} = 1 + 2\pi \frac{M_x}{H_x} \frac{\omega_0^2 (\omega_0^2 - \omega^2 + \gamma^2 + 2i\gamma\omega)}{(\omega_0^2 - \omega^2 + \gamma^2)^2 + 4\gamma^2 \omega^2}. \quad (13)$$

In particular, during the part of the precession cycle when the magnetization M_x is antialigned with $B_x \approx H_x$, $Im(n) < 0$, and a propagating wave $H_{0y} e^{i\omega(nz/c-t)}$ is amplified during its passage through the medium.

It appears difficult to realize the desired precession of \mathbf{M} about the y axis as suggested, since B_y would have to reach full strength in less than the damping time $1/\gamma$, and no actual laser has (I believe) been built utilizing a magnetic medium. The interest of this problem is in providing a classical viewpoint of how wave amplification is possible in principle by preparing a medium in an optically active state.

References

- [1] I.I. Rabi, *Space Quantization in a Gyrating Magnetic Field*, Phys. Rev. **51**, 4652 (1937), http://puhep1.princeton.edu/~mcdonald/examples/QM/rabi_pr_51_652_37.pdf

- [2] F. Bloch, *Nuclear Induction*, Phys. Rev. **70**, 460 (1946),
http://puhep1.princeton.edu/~mcdonald/examples/QM/bloch_pr_70_460_46.pdf
- [3] R.H. Dicke, *Coherence in Spontaneous Radiation Processes*, Phys. Rev. **93**, 99 (1954),
http://puhep1.princeton.edu/~mcdonald/examples/QM/dicke_pr_93_99_54.pdf